

Product: 1-26.5Ghz 4Way power divider

Part Number: LPD-1/26.5-4S



| Specification |                             |                          |         |         |       |
|---------------|-----------------------------|--------------------------|---------|---------|-------|
| No.           | Parameter                   | Minimum                  | Typical | Maximum | Units |
| 1             | Frequency range             | 1                        | -       | 26.5    | GHz   |
| 2             | Insertion Loss              | -                        | -       | 3.3     | dB    |
| 3             | Phase Balance:              | -                        | -       | ±5      | dB    |
| 4             | Amplitude Balance           | -                        | -       | ±0.5    | dB    |
| 5             | Isolation                   | 18                       | -       |         | dB    |
| 6             | VSWR                        | -                        | -       | 1.6     | -     |
| 7             | Power                       |                          |         | 20      | W cw  |
| 8             | Operating Temperature Range | -40                      | -       | +85     | °C    |
| 9             | Impedance                   | -                        | 50      | -       | Ω     |
| 10            | Connector                   | SMA-F                    |         |         |       |
| 11            | Preferred finish            | Black/Sliver/yellow/blue |         |         |       |

**Remarks:**

1. Not include Theoretical loss 6db 2.Power rating is for load vswr better than 1.20:1

| Environmental Specifications |  |
|------------------------------|--|
| Operational Temperature      | -40°C~+85°C  |
| Storage Temperature          | -50°C~+105°C   |
| Altitude                     | 30,000 ft. (Epoxy Sealed Controlled environment)                                 |
|                              | 60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional) |
| Vibration                    | 25gRMS (15 degrees 2KHz) endurance, 1 hour per axis                              |
| Humidity                     | 100% RH at 35°C, 95%RH at 40°C   |
| Shock                        | 20G for 11msec half sine wave,3 axis both directions                             |
| Mechanical Specifications    |  |
| Housing                      | Aluminum   |
| Connector                    | Passivated or stainless steel  |
| Female Contact:              | gold plated beryllium brass  |
| Rohs                         | compliant  |
| Weight                       | 0.2kg  |

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000


## Outline Drawing:

All Dimensions in mm

Outline Tolerances  $\pm 0.5(0.02)$

Mounting Holes Tolerances  $\pm 0.2(0.008)$

All Connectors: SMA-Female



## TEST DATA

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd


电话: 028-65199117 传真: 028-65199116

http://www.leadermicrowave.com sales@leader-mw.com

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000



成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd


电话: 028-65199117 传真: 028-65199116

http://www.leadermicrowave.com sales@leader-mw.com

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000



成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd


电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000



成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

http://www.leadermicrowave.com sales@leader-mw.com

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000