

Product: Band Pass filter

Part Number: LBF-1575/100-2S



Specification					
No.	Parameter	Minimum	Typical	Maximum	Units
1	Center Freq.		1575		MHz
2	Pass band	1525	-	1625	Mhz
3	Insertion Loss at Center Freq.			0.5	dB
4	Rejection	≥50dB@DC-1425Mhz ≥50dB@1725-3000Mhz			dB
5	VSWR	-		1.3	-
6	Power			50w	W cw
7	Operating Temperature Range	-35	-	+65	°C
8	Impedance	-	50	-	Ω
9	Connecter	SMA-F			
10	Preferred finish	black			

**Remarks:**

.Power rating is for load vswr better than 1.20:1

Environmental Specifications	
Operational Temperature	0°C~+60°C
Storage Temperature	-50°C~+85°C
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions
Mechanical Specifications	
Housing	Aluminum
Connector	ternary alloy three-part alloy
Female Contact:	gold plated beryllium bronze
Rohs	compliant
Weight	0.1kg

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000


## Outline Drawing:

All Dimensions in mm


Outline Tolerances  $\pm 0.5(0.02)$

Mounting Holes Tolerances  $\pm 0.2(0.008)$

All Connectors: SMA-Female



## Test data



成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000