

Product: Band Pass filter

Part Number: LBF-2/6-2S



Specification					
No.	Parameter	Minimum	Typical	Maximum	Units
1	Center Freq.		4000		MHz
2	Pass band	2000	-	6000	Mhz
3	Insertion Loss at Center Freq.			1.5	dB
4	Rejection	≥45dB@DC-1.65Ghz, ≥30dB@6.65-12Ghz			dB
5	VSWR	-		1.6	-
6	Power			0.5w	W cw
7	Operating Temperature Range	-35	-	+50	°C
8	Impedance	-	50	-	Ω
9	Connecter	SMA-F			
10	Preferred finish	black			

Remarks:

.Power rating is for load vswr better than 1.20:1

Environmental Specifications	
Operational Temperature	-350°C~+60°C
Storage Temperature	-50°C~+85°C
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions
Mechanical Specifications	
Housing	Aluminum
Connector	ternary alloy three-part alloy
Female Contact:	gold plated beryllium bronze
Rohs	compliant
Weight	0.1kg

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> sales@leader-mw.com

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000


Outline Drawing:

All Dimensions in mm


Outline Tolerances $\pm 0.5(0.02)$

Mounting Holes Tolerances $\pm 0.2(0.008)$

All Connectors: SMA-Female



Test data



成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> sales@leader-mw.com

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000