

Product: dual directional Coupler

Part Number: LDDC-0.5/40-10s



Specification					
No.	Parameter	Minimum	Typical	Maximum	Units
1	Frequency range	0.5		40	GHz
2	Nominal Coupling		10		dB
3	Coupling Accuracy			± 1.5	dB
4	Coupling Sensitivity to Frequency			± 1.2	dB
5	Insertion Loss			6.0	dB
6	Directivity	10			dB
7	VSWR			1.7	:1
8	Power			20	W
9	Operating Temperature Range	-32		+85	°C
10	Impedance	-	50	-	Ω
11	Connector	2.92-F			
12	Preferred finish	Yellow/black			

**Remarks:**

1.Include Theoretical loss 0.46db 2.Power rating is for load vswr better than 1.20:1

Environmental Specifications	
Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+95°C
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions
Mechanical Specifications	
Housing	Aluminum
Connector	Stainless steel
Female Contact:	gold plated beryllium brass
Rohs	compliant
Weight	0.15kg

**Outline Drawing:**

All Dimensions in mm

Outline Tolerances ± 0.5(0.02)

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)


TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000

Mounting Holes Tolerances  $\pm 0.2(0.008)$

All Connectors: 2.92-Female



TEST DATA

成都利德尔科技有限公司 ChengDu Leader Microwave Technology Co.,Ltd

电话: 028-65199117 传真: 028-65199116

<http://www.leadermicrowave.com> [sales@leader-mw.com](mailto:sales@leader-mw.com)

TEL: +86-28-65199117 FAX: +86-28-65199116

Add: 中国 成都市成华区华翰路 89 号 610000

No.89,Huahan Road, chenghua Zone Chengdu, Sichuan China Zip Code:610000